



IMR-150 SERIES

150W Single Output Industrial type DIN Rail Power Supply



- only industrial type power supply
- Standard/Din Rail Mounting Dual Purpose
- Easy mounting (one-step installation)
- No-load Consumption is lower than 0.5W (No Display)
- " Output Voltage Monitor " Display (Optional)
- 100% burn-in test
- 2 years warranty

CLASS A

WARNING: *Operation of this equipment in a residential environment could cause radio interference.*

DIMENSIONS: 100(H)*83(D)*49(W)mm

WEIGHTS: 390g

General specifications

INPUT

Input range 90~132/180~264VAC(Selectable)
220~380VDC
Input frequency 47~63Hz
Inrush current (25°C) 20A/110VAC
40A/220VAC

OUTPUT

Hold-up time 13ms
Short protection Autorecovery
Over load protection Automatic power limited
Optional 5V/3A AUX output for models which output voltage lower than 40VDC

Detail specifications

150 Watts

MODEL	Adj. ± %	1			& Noise 4	REG. 2	REG. 3	Efficiency 5	O.V.P
		Min.	Rated	Max.					
IMR-150-12	V : +12V ±10%	0A	12.5A	12.5A	120mV	±1%	±1%	85% Ref.	17.1 ~ 18.9V
IMR-150-24	V : +24V ±10%	0A	6.25A	6.25A	240mV	±1%	±1%	86% Ref.	31.4 ~ 34.7V

Please Choose Fit Function, And Fill In The Blank With Suitable Words.

Order Model: LP1500D-24M

Optional Function:

Terminal Block: " " : PCB Barrier Terminal Block

"E" : Mini Terminal Block

Monitor: " " : No Monitor

"D" : Monitor Display

Type: " " : No Display Function

"A" : Output Voltage Display

